

NEW WORK ITEM PROPOSAL

Proposer Secretariat of TC80	Date of proposal 2011-06-21
TC/SC TC80	Secretariat UK
Date of circulation 2011-07-01	Closing date for voting 2011-10-07

A proposal for a new work item within the scope of an existing technical committee or subcommittee shall be submitted to the Central Office. The proposal will be distributed to the P-members of the technical committee or subcommittee for voting on the introduction of it into the work programme, and to the O-members for information. The proposer may be a National Committee of the IEC, the secretariat itself, another technical committee or subcommittee, an organization in liaison, the Standardization Management Board or one of the advisory committees, or the General Secretary. Guidelines for proposing and justifying a new work item are given in ISO/IEC Directives, Part 1, Annex C (see extract overleaf). **This form is not to be used for amendments or revisions to existing publications.**

The proposal (to be completed by the proposer)

Title of proposal Future IEC 61097-15 Ed.1: GLOBAL MARITIME DISTRESS AND SAFETY SYSTEM (GMDSS) – Part 15: Inmarsat FB500 ship earth station – Operational and performance requirements, methods of testing and required test results		
<input checked="" type="checkbox"/> Standard	<input type="checkbox"/> Technical Specification	
Scope (as defined in ISO/IEC Directives, Part 2, 6.2.1) To develop an International standard for a Inmarsat Fleet Broadband ship earth station which is intended to be used at sea within the Global Maritime Distress and Safety System (GMDSS).		
Purpose and justification , including the market relevance, whether it is a proposed horizontal standard (Guide 108) ¹⁾ and relationship to Safety (Guide 104), EMC (Guide 107), Environmental aspects (Guide 109) and Quality assurance (Guide 102) . (attach a separate page as annex, if necessary) Inmarsat offers new services on its system as technology advances. The original Inmarsat A service which was analogue has been phased out and the first digital system, Inmarsat B, is now in the process of being phased out. Current Inmarsat services include Inmarsat Fleet and the newer Inmarsat Fleet Broadband, IEC has a standard for Inmarsat Fleet (IEC 61097-13). This new standard is intended for Inmarsat Fleet Broadband, Inmarsat satellite terminals are widely carried by merchant ships and the use of Fleet Broadband is rapidly growing. The technical details for Fleet Broadband are published by Inmarsat and shipborne terminals require Inmarsat type approval before they are allowed access to the Inmarsat network. For operation within the GMDSS further approval is required by Administrations in order to show compliance with IMO performance standards. The new standard contains the requirements and test methods additional to Inmarsat type approval to demonstrate compliance with the IMO requirements. The text is similar to that in IEC 61097-13 for Inmarsat Fleet as the IMO requirements are the same.		
Target date	for CDV 2011-06	for IS/ TS 2012-12
Estimated number of meetings 1	Frequency of meetings: 1 per year	Date and place of first meeting: To be decided
Proposed working methods	<input type="checkbox"/> E-mail	<input checked="" type="checkbox"/> Collaboration tools
Relevant documents to be considered 80/636/CDV has been prepared by Inmarsat		
Relationship of project to activities of other international bodies The project supports the requirements for type approval of ship borne equipment contained in the International Convention on the safety of Life at Sea (SOLAS) of the International Maritime Organization.		
Liaison organizations IMO, CIRM	Need for coordination within ISO or IEC	

Copyright © 2011 International Electrotechnical Commission, IEC. All rights reserved. It is permitted to download this electronic file, to make a copy and to print out the content for the sole purpose of preparing National Committee positions. You may not copy or "mirror" the file or printed version of the document, or any part of it, for any other purpose without permission in writing from IEC.

Preparatory work	
Ensure that all copyright issues are identified. Check one of the two following boxes <input checked="" type="checkbox"/> A draft is attached for comment* <input type="checkbox"/> An outline is attached	
* Recipients of this document are invited to submit, with their comments, notification of any relevant patent rights of which they are aware and to provide supporting documentation.	
We nominate a project leader as follows in accordance with ISO/IEC Directives, Part 1, 2.3.4 (name, address, fax and e-mail): Peter Blackhurst, Inmarsat, 99 City Road, London, EC1Y 1AX, UK peter_blackhurst@inmarsat.com	
Concerns known patented items (see ISO/IEC Directives, Part 2)	Name and/or signature of the proposer
<input type="checkbox"/> Yes. If yes, provide full information as an annex <input checked="" type="checkbox"/> no	Kim Fisher
Comments and recommendations from the TC/SC officers	
1) Work allocation <input type="checkbox"/> Project team <input checked="" type="checkbox"/> New working group <input type="checkbox"/> Existing working group no:	
2) Draft suitable for direct submission as <input type="checkbox"/> CD <input checked="" type="checkbox"/> CDV/ DTS	
3) General quality of the draft (conformity to ISO/IEC Directives, Part 2) <input checked="" type="checkbox"/> Little redrafting needed <input type="checkbox"/> Substantial redrafting needed <input type="checkbox"/> no draft (outline only)	
4) Relationship with other activities In IEC The proposed standard is consistent with the existing work of TC80 of developing international technical standards for equipment and systems that are part of the mandatory carriage requirements of the Conventions of the IMO. In other organizations	
5) Proposed horizontal standard <input type="checkbox"/> ¹⁾ Other TC/SCs are requested to indicate their interest, if any, in this NP to the TC/SC secretary.	
Remarks from the TC/SC officers Due to the timeliness of this project, Inmarsat has prepared a CDV. The present NWIP and the associated CDV (80/636/CDV) are circulated in parallel. IEC national committees are requested to appoint/confirm experts willing to participate in the development of this project. If the NP is not approved, the CDV ballot will be cancelled immediately	

Approval criteria:

- Approval of the work item by a simple majority of the P-members voting;
- At least 4 P-members in the case of a committee with 16 or fewer P-members, or at least 5 P-members in the case of committees with more than 17 P-members, have nominated or confirmed the name of an expert and approved the new work item proposal.

Elements to be clarified when proposing a new work item

Title

Indicate the subject matter of the proposed new standard or technical specification.

Indicate whether it is intended to prepare a standard or a technical specification.

Scope

Give a clear indication of the coverage of the proposed new work item and, if necessary for clarity, exclusions.

Indicate whether the subject proposed relates to one or more of the fields of safety, EMC, the environment or quality assurance.

Purpose and justification

Give details based on a critical study of the following elements wherever practicable.

- The specific aims and reason for the standardization activity, with particular emphasis on the aspects of standardization to be covered, the problems it is expected to solve or the difficulties it is intended to overcome.
- The main interests that might benefit from or be affected by the activity, such as industry, consumers, trade, governments, distributors.
- Feasibility of the activity: Are there factors that could hinder the successful establishment or general application of the standard?
- Timeliness of the standard to be produced: Is the technology reasonably stabilized? If not, how much time is likely to be available before advances in technology may render the proposed standard outdated? Is the proposed standard required as a basis for the future development of the technology in question?
- Urgency of the activity, considering the needs of the market (industry, consumers, trade, governments etc.) as well as other fields or organizations. Indicate target date and, when a series of standards is proposed, suggest priorities.
- The benefits to be gained by the implementation of the proposed standard; alternatively, the loss or disadvantage(s) if no standard is established within a reasonable time. Data such as product volume or value of trade should be included and quantified.
- If the standardization activity is, or is likely to be, the subject of regulations or to require the harmonization of existing regulations, this should be indicated.

If a series of new work items is proposed, the purpose and justification of which is common, a common proposal may be drafted including all elements to be clarified and enumerating the titles and scopes of each individual item.

Relevant documents

List any known relevant documents (such as standards and regulations), regardless of their source. When the proposer considers that an existing well-established document may be acceptable as a standard (with or without amendments), indicate this with appropriate justification and attach a copy to the proposal.

Cooperation and liaison

List relevant organizations or bodies with which cooperation and liaison should exist.

Preparatory work

Indicate the name of the project leader nominated by the proposer.

CONTENTS

1	Scope.....	6
2	Normative references	6
3	Definitions and abbreviations.....	7
3.1	Definitions	7
3.2	Abbreviations	8
4	General and operational requirements.....	9
4.1	General.....	9
4.2	Inmarsat type approval.....	9
4.3	Prevention of alteration of ship earth station identity	9
4.4	Initiation of distress alerts	9
4.5	Dedicated distress button.....	9
4.6	Alarm on reception of shore-originated duplex calls with distress priority.....	10
4.7	Radio frequency hazards.....	10
4.8	Equipment manual.....	10
5	Technical requirements	11
5.1	Introduction	11
5.2	Pre-emption by distress calls (ship originated)	11
5.3	Power supply interruption	11
5.4	Interfaces	11
6	Methods of testing and required test results	11
6.1	General.....	11
6.2	General requirements.....	13
6.3	Prevention of alteration of ship earth station identity	13
6.4	Distress alerts	13
6.5	Distress priority alarm	14
6.6	Labels and manual.....	14
6.7	Operational tests (without pre-emption).....	14
6.8	Operational tests (with pre-emption).....	15
6.9	Power supply.....	19
6.10	Interfaces	20
Annex A	(normative) Requirements relating to installation	21
A.1	Power supply.....	21
A.2	Antenna siting	21
Annex B	(informative) Reception of maritime safety information (MSI)	22
Annex C	(informative) List of Inmarsat FB500 type-approval tests	23
	Bibliography.....	24
	Table 1 – Testing with different priorities	14
	Table 2 – Pre-emption of telephone call set up from ship	16
	Table 3 – Pre-emption of telephone call set up from shore.....	17
	Table 4 – Pre-emption of facsimile call set up from ship.....	17
	Table 5 – Pre-emption of facsimile call set up from shore	18
	Table 6 – Pre-emption of 64 kbit/s call set up from ship	18
	Table 7 – Pre-emption of 64 kbit/s call set up from shore.....	18
	Table 8 – Pre-emption of 3,1k audio call set up from ship	18

Table 9 – Pre-emption of 3,1k audio call set up from shore	19
Table 10 – Non-pre-emption of high-priority ship-originated telephone call by subsequent lower priority ship-originated calls	19
Table 11 – Non-pre-emption of high-priority shore-originated telephone call by subsequent lower priority ship-originated calls	19
Table C.1 – List of Inmarsat tests	23

INTERNATIONAL ELECTROTECHNICAL COMMISSION

**GLOBAL MARITIME DISTRESS AND
SAFETY SYSTEM (GMDSS) –**
**Part 15: Inmarsat FB500 ship earth station –
Operational and performance requirements,
methods of testing and required test results**

FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC provides no marking procedure to indicate its approval and cannot be rendered responsible for any equipment declared to be in conformity with an IEC Publication.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

International Standard IEC 61097-15 has been prepared by IEC technical committee 80: Maritime navigation and radiocommunication equipment and systems.

The text of this standard is based on the following documents:

FDIS	Report on voting
80/XXX/FDIS	80/XXX/RVD

Full information on the voting for the approval of this standard can be found in the report on voting indicated in the above table.

This publication has been drafted in accordance with the ISO/IEC Directives, Part 2.

A list of all parts of IEC 61097 series, published under the general title *Global maritime distress and safety system (GMDSS)*, can be found on the IEC website.

The committee has decided that the contents of this publication will remain unchanged until the maintenance result date¹⁾ indicated on the IEC web site under "<http://webstore.iec.ch>" in the data related to the specific publication. At this date, the publication will be

- reconfirmed,
- withdrawn,
- replaced by a revised edition, or
- amended.

A bilingual version of this publication may be issued at a later date.

1) The National Committees are requested to note that for this publication the maintenance result date is 2015.

GLOBAL MARITIME DISTRESS AND SAFETY SYSTEM (GMDSS) –

Part 15: Inmarsat FB500 ship earth station – Operational and performance requirements, methods of testing and required test results

1 Scope

This part of IEC 61097 specifies the minimum operational and performance requirements, technical characteristics, methods of testing and required test results for Inmarsat FB500 ship earth stations (SES), capable of transmitting and receiving distress and safety communications, initiating and receiving distress priority calls and transmitting and receiving general radiocommunications, using radiotelephony (voice), as required within Regulation IV/10.1 and 14.1 of the 1988 amendments to the 1974 International Convention for the Safety of Life at Sea (SOLAS), for use in the GMDSS.

This standard covers equipment construction and testing. Matters relating to installation are reproduced in Annex A.

NOTE The Inmarsat FB500 is intended to meet the voice requirements of IMO Resolution A.1001(25). In order to meet the GMDSS carriage requirements of SOLAS in respect of receipt of SafetyNET broadcasts and direct printing telegraphy, it is necessary to install a combined Inmarsat C/EGC transceiver in addition to the Inmarsat FB500 equipment. Annex B provides more information.

This standard incorporates the performance standards of IMO Resolution MSC.130(75) and also takes into account the priority access (voice pre-emption) requirements of IMO Resolution A.1001(25). This standard takes account of IMO Resolution A.694(17) to which is associated IEC 60945. When a requirement in this standard is different from IEC 60945, the requirement in this standard shall take precedence.

All text of this standard, whose wording is identical to that in the IMO Resolutions is printed in italics and the Resolution and paragraph number indicated between brackets.

Responsibility for type approval of Inmarsat FB500 is vested in Inmarsat by IMO Resolution MSC.130(75) (see 4.2). Therefore, this standard does not reproduce Inmarsat test procedures in full, but refers to the relevant tests in Annex C. It is recommended that equipment manufacturers rationalize the test requirements of this standard and those of Inmarsat before embarking on the approval process.

2 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 60945, *Maritime navigation and radiocommunication equipment and systems – General requirements – Methods of testing and required test results*

IEC 61162 (all parts), *Maritime navigation and radio communication equipment and systems – Digital interfaces*

IEC 61162-1, *Maritime navigation and radio communication equipment and systems – Digital interfaces – Part 1: Single talker and multiple listeners*

ISO/IEC 17025, *General requirements for the competence of testing and calibration laboratories*

IMO, *International Convention for the safety of life at sea (SOLAS), 1974 as amended*

IMO Resolution A.694(17), *General requirements for shipborne radio equipment forming part of the global maritime distress and safety system (GMDSS) and for electronic navigational aids*

IMO Resolution A.1001(25), *Criteria for the provision of mobile-satellite communication systems in the Global Maritime Distress and Safety System (GMDSS)*

IMO Resolution MSC.130(75), *Performance standards for Inmarsat ship earth stations capable of two-way communications*

Inmarsat *BGAN SDM Change Note No. 10 or higher*

ITU *Radio Regulations*

3 Definitions and abbreviations

3.1 Definitions

For the purposes of this International Standard, the following definitions apply.

3.1.1

BGAN physical layer test-set (BPLT)

item of test equipment designed to simulate the combined operation of an Inmarsat satellite and an Inmarsat FB500 Radio Access Network. The BPLT interfaces to the EUT at L-band, either by means of a small antenna or via coaxial cable. Together with the TCM it permits voice calls to be set up in accordance with the relevant Inmarsat FB500 protocols

3.1.2

Inmarsat priorities

priority 3 = distress priority, 2 = urgency priority, 1 = safety priority, 0 = routine

3.1.3

Inmarsat type approval

testing of a ship earth station design by Inmarsat. This approval is required for access to the Inmarsat space segment and is essential before approvals can be granted by national administrations

3.1.4

L-band

frequency band in the range 1,4 GHz to 1,7 GHz allocated to the mobile satellite service and in which the EUT transmits and receives

3.1.5

necessary bandwidth

for a given class of emission, width of the frequency band which is just sufficient to ensure the transmission of information at the rate and with the quality required under specified conditions

3.1.6

performance check

for the purpose defined in IEC 60945, check comprising standard tests A and B

3.1.7**performance test**

for the purpose defined in IEC 60945, test comprising standard tests A and B, carried out for both distress and safety priorities

3.1.8**pre-emption**

automatic clearance of an ongoing call to enable a call of higher priority to be established

3.1.9**radio frequency hazards**

hazards caused by electromagnetic radiofrequency radiation, the level of which would require safety rules to be applied in the vicinity of the radiating equipment

3.1.10**radome**

radiofrequency transparent cover placed over an antenna system

3.1.11**SafetyNET**

service provided over a dedicated Inmarsat C carrier, for the dissemination of maritime safety information, such as distress alerts, weather forecasts and coastal warnings

3.1.12**standard tests**

two tests defined in this document as Test A – Duplex telephone test (ship-originated) and Test B – Duplex telephone test (shore-originated) which together form the performance test required by IEC 60945

3.1.13**TCM (Test Case Manager)**

Protocol tester used for BGAN type approval. This together with the BPLT will allow for validation of the FB500 protocol.

3.2 Abbreviations

BPLT	BGAN Physical layer test-set
EGC	Enhanced group call
EIRP	Effective isotropic radiated power
EUT	Equipment under test
GMDSS	Global maritime distress and safety system
IMO	International Maritime Organization
Inmarsat	Inmarsat Global Ltd.
ISO	International Organization for Standardization
ITU	International Telecommunications Union
MSI	Maritime safety information
NAS	Non-access stratum (a 3 rd Generation Partnership Project standard)
RAN	Radio access network
RCC	Rescue coordination centre
SDM	System definition manual (published by Inmarsat)
SES	Ship earth station
SOLAS	International convention for the safety of life at sea

UT User Terminal

4 General and operational requirements

4.1 General

(See 6.2)

(MSC.130/A.1) *The ship earth station installation capable of telephony and data communications shall comply with the general requirements set out in resolution A.694(17) and with the following minimum requirements.*

An Inmarsat FB500 ship earth station, which is defined in the Inmarsat BGAN SDM, is capable of:

- transmitting and receiving distress and safety communications;
- initiating and receiving distress priority calls; and
- transmitting and receiving general radio communications, using radiotelephony.

The equipment shall comply with the general requirements of IEC 60945, as applicable to the equipment category, for example “protected”, “exposed”.

4.2 Inmarsat type approval

(MSC.130/A.2) *The equipment shall be type approved by Inmarsat and shall comply with the environmental conditions specified in its technical requirements for Inmarsat ship earth stations capable of two-way communications.*

NOTE Inmarsat type approval is required for access to the Inmarsat space segment and is essential before approvals can be granted by national administrations.

4.3 Prevention of alteration of ship earth station identity

(See 6.3)

(MSC.130/A3.1) *No control external to the equipment shall be available for alteration of the ship station identity.*

4.4 Initiation of distress alerts

(See 6.4)

(MSC.130/A.3.2) *It shall be possible to initiate and make distress calls by telephony or data communications from the position at which the ship is normally navigated and from any position designated for distress alerting. In addition, where a room is provided for radio communications, means to initiate distress calls shall also be fitted in that room.*

A suitable interface on the EUT to enable these two requirements to be achieved shall be provided by the equipment manufacturer.

4.5 Dedicated distress button

(See 6.4)

(MSC.130/A3.5) *A distress call shall be activated only by means of a dedicated distress button. This button shall not be any key of an ITU-T digital input panel or an ISO keyboard provided on the equipment.*

(MSC.130/A3.6) *The dedicated distress button shall:*

- 1 *be clearly identified; and*

2 *be protected against inadvertent operation.*

(MSC.130/A3.7) *The distress alert initiation shall require at least two independent actions.*

(MSC.130/A3.4) *It shall be possible to interrupt and initiate distress messages at any time.*

NOTE Inmarsat FB500 Service definition provides the following clarification. The UT should ensure that selection of Maritime Distress priority shall not become effective until the switch contacts have been continuously held closed for a period of at least 6 s.

Audible and visible indications shall be made at all positions from where a distress call may be initiated, irrespective of the telephone terminal from which the distress call is originated. The visible indications shall continue until reset manually. It shall be possible to initiate further distress calls without re-setting the first indication. During performance testing with distress priority, indications shall be identical to those generated by initiation of a real distress call.

4.6 Alarm on reception of shore-originated duplex calls with distress priority

(See 6.5)

(MSC.130/A.3.3) *Where no other means of receiving distress, urgency and safety broadcasts or an additional distress alert relay are provided and existing levels of aural signals produced by the telephone or printer are considered to be inadequate, the ship earth station equipment shall provide an aural/visual alarm of appropriate level.*

An output shall be provided to actuate an external aural/visual alarm on the receipt of a distress priority duplex call.

NOTE Distress, urgency and safety broadcasts are received by associated Inmarsat-C/EGC receiving equipment – see Annex B.

4.7 Radio frequency hazards

(See 6.6)

(MSC.130/A.4) *In order to permit warnings of potential hazards to be displayed in appropriate places, a label shall be attached to the radome by the equipment manufacturer, indicating the distance at which radiation levels of 100 W/m², 25 W/m² and 10 W/m² exist.*

The label shall have characters at least 10 mm high. The maximum distance from the EUT at which the power density level of 100 W/m² has been measured by the equipment manufacturer shall be included in the equipment manual. The power density at this distance shall be re-measured and the level specified in the equipment manual and on the label confirmed.

4.8 Equipment manual

(See 6.6)

In addition to the requirements of IEC 60945 the manual shall contain information for the installation to comply with IMO requirements as detailed in Annex A.

The manual shall also address the issue of reception of maritime safety information (MSI) (see Annex B).

The manual shall also include a cautionary note to the effect that, before clearance of a distress priority call is initiated, the RCC shall be advised as to why the call is being cleared.

The manual shall include the maximum distance from the radome at which a power density of 100 W/m² has been measured by the manufacturer of the EUT.

5 Technical requirements

5.1 Introduction

IMO Resolution MSC.130(75) appoints Inmarsat as the type approval authority for Inmarsat FB500 SES (see 4.2). The Inmarsat BGAN SDM is, therefore, the primary source of technical characteristics for Inmarsat FB500 SES for use in the GMDSS, but the following amendments and additions shall apply.

5.2 Pre-emption by distress calls (ship originated)

(See 6.7, 6.8)

On initiation of a distress priority call the EUT shall interrupt any on-going call of lower priority, if necessary, and then set up the distress priority call automatically.

5.3 Power supply interruption

(See 6.9)

(MSC.130/5.2) Changing from one source of supply to another or any interruption up to 60 s of the supply of electrical energy shall not render the equipment inoperative or require the equipment to be manually re-initialized.

Programmable functions stored in memory shall not be lost on power-down and power-up of the equipment.

5.4 Interfaces

(See 6.10)

Inmarsat FB500 equipment has no mandatory requirements for interfaces. However If interfaces to external sensors and sources are provided, which comply with IMO Resolutions and ITU Recommendations, they shall comply with the IEC 61162 series.

Any additional interface capability used to meet a required interface in the absence of an appropriate IEC 61162 series interface, for example, proprietary input or output sentences, shall be fully documented.

Any critical or unique interface characteristics, for example, timing, resulting actions or equipment behaviour due to receiving or transmitting a sentence, which are additional to those specified in the IEC interface standard, shall be fully documented.

6 Methods of testing and required test results

6.1 General

6.1.1 Test arrangements

The requirements of this clause are in addition to the Inmarsat requirements for type approval, given in the Inmarsat BGAN SDM Change Note 10 (or higher). The manufacturer shall, unless otherwise agreed, set up the equipment and ensure it is operating normally before testing commences. If the test site used for type approval is also an accepted Inmarsat test facility, both series of tests may be combined, with the prior agreement of Inmarsat and the national test authority.

After successful completion of the Inmarsat Phase I tests (see Inmarsat BGAN SDM) compliance with the requirements of this standard shall be demonstrated by carrying out the tests described in the following. These tests shall be conducted using a BPLT and TCM or an alternative method of functionally achieving the same result.

Verification of compliance with the technical requirements is provided by performance tests or performance checks at normal test conditions unless otherwise stated.

6.1.2 Measurement uncertainties

Measurement uncertainty shall be calculated and techniques employed to minimize its range. This uncertainty shall be applied to the limit and any measurement falling below the range is deemed acceptable. See ISO/IEC 17025.

6.1.3 Definition of standard tests

Standard tests comprise the setting-up and clearing-down of telephone calls with different priorities, with a subjective check of the circuit quality.

NOTE Definitions of operating conditions and quality of circuits can be found in ITU-R Recommendation BS 1284.

Test A: Duplex telephone test (ship originated)

The EUT operator shall set up a duplex telephone channel with the appropriate priority.

The EUT operator shall say clearly:

“This is the EUT operator performing test A, alpha. Please report my speech quality. Over”

The BPLT operator shall reply:

“This is the BPLT operator performing test A, alpha. Your speech quality is good/poor. Please report my speech quality. Over”

The EUT operator shall reply:

“Your speech quality is good/poor. I am now clearing the channel. Over”

The EUT operator shall clear the call.

Test B: duplex telephone test (shore originated)

The BPLT operator shall set up a duplex telephone channel with the appropriate priority.

The BPLT operator shall say clearly:

“This is the BPLT operator performing test B, bravo. Please report my speech quality. Over”

The EUT operator shall reply:

“This is the EUT operator performing test B, bravo. Your speech quality is good/poor. Please report my speech quality. Over”

The BPLT operator shall reply:

“Your speech quality is good/poor. I am now clearing the channel. Over”

The BPLT operator shall clear the call.

6.1.4 Required results from standard tests

For the performance checks and tests in A and B for voice communication, calls shall be set up and cleared down satisfactorily. The correct priority shall be received at the BPLT or the EUT as appropriate. Voice quality shall be good in both directions and it shall be possible to distinguish clearly the content of the voice messages.

6.2 General requirements

The equipment shall be tested for compliance with the requirements of IEC 60945.

The manufacturer shall state which items of equipment are classified as exposed and which are protected. The equipment normally protected by a radome shall be tested with the radome *in situ* under the “exposed” environmental conditions stated in IEC 60945.

A performance check or test shall normally consist of telephony tests between the EUT and an Inmarsat BPLT- TCM. Alternatively this may be verified by performing loop back tests.

For the purposes defined in IEC 60945:

Performance check: shall comprise standard tests A and B, carried out for distress priority only.

Performance test: shall comprise standard tests A and B, carried out for both distress and safety priorities.

NOTE See 6.8 for the test for immunity to power supply failure.

6.3 Prevention of alteration of ship earth station identity

(See 4.3)

Check by observation of the equipment and inspection of manufacturer’s documentation that there is no control external to the equipment which can enable the ship earth station identity to be altered.

6.4 Distress alerts

(See 4.4, 4.5)

6.4.1 Distress initiation

Check by observation of the equipment and inspection of manufacturer’s documentation that the equipment has interfaces suitable to enable the initiation and making of distress calls from two different positions.

Check by observation that dedicated distress buttons are provided with the equipment and confirm by observation that their design and operation complies with the requirements for distress alert in IEC 60945.

Confirm by observation that when a distress button is operated the audible and visible indications are made at all the positions from which distress calls can be made.

Confirm by observation that facilities have been provided to reset visual indications at all the positions from which distress calls can be made.

6.4.2 Test using local distress button

6.4.2.1 Purpose

This test checks the operation of the EUT when setting up a distress call using the local distress button and subsequently clearing it down by whatever means.

6.4.2.2 Method of test

See tests in 6.7 and 6.8 for operational tests.

6.4.2.3 Required results

Results shall be in accordance with 6.1.4.

6.4.3 Test using remote distress button

6.4.3.1 Purpose

This test checks the operation of the EUT when setting up a distress call using the remote distress button and subsequently clearing it down by whatever means.

6.4.3.2 Method of test

Test A shall be performed using distress priority, the call being set up using a remote distress button, located at least 10 m away from the EUT.

6.4.3.3 Required results

Results shall be in accordance with 6.1.4.

6.5 Distress priority alarm

(See 4.6)

Check by observation that the equipment is provided with an interface for an external alarm.

By connecting a suitable alarm to the interface check by observation that the alarm is activated on receipt of a distress priority duplex call.

6.6 Labels and manual

(See 4.7, 4.8)

Confirm by observation that the required information is provided on a label and that the required information is provided in the equipment manual.

6.7 Operational tests (without pre-emption)

(See 5.2)

6.7.1 Purpose

These tests ensure that shore-originated and ship-originated calls can be set up with different priorities and subsequently cleared down.

6.7.2 Method of test

The following combination of standard tests and priorities shall be performed.

Table 1 – Testing with different priorities

Test	Priority
Test A	Distress priority (3) ^a
Test A	Urgency priority (2)
Test A	Safety priority (1)

Test A	Routine priority (0)
Test B	Distress priority (3)
Test B	Urgency priority (2)
Test B	Safety priority (1)
Test B	Routine priority (0)
^a This test call shall be set up using a “local” distress button designed to be co-located with the EUT.	

6.7.3 Required results

Results shall be in accordance with 6.1.4.

6.8 Operational tests (with pre-emption)

(See 5.2)

6.8.1 Purpose

These tests are to verify correct pre-emption of lower priority calls by calls of higher priority.

6.8.2 Method of test

NOTE Only pre-emption by ship-originated calls is tested here. Pre-emption by shore-originated calls has been tested by Inmarsat during Inmarsat FB500 infrastructure commissioning.

All priority 3 tests shall be set up from the local distress button.

- a) Duplex telephone calls shall be set up from the EUT with each of the priorities (0, 1, 2, 3) shown in column 1 of Table 2. Test A shall then be performed with all of the priorities (0, 1, 2, 3) shown in column 2, without first clearing the original call in progress. The required outcomes are shown in column 3.
- b) Duplex telephone calls shall be set up from the BPLT-TCM with each of the priorities (0, 1, 2, 3) shown in column 1 of Table 3. Test A shall then be performed with all of the priorities (0, 1, 2, 3) shown in column 2, without first clearing the original call in progress. The required outcomes are shown in column 3.
- c) Duplex facsimile calls shall be set up from the EUT each with priority 0 (only priority available) as shown in column 1 of Table 4. Test A shall then be performed with all of the priorities (0, 1, 2, 3) shown in column 2, without first clearing the original call in progress. The required outcomes are shown in column 3.
- d) Duplex facsimile calls shall be set up from the BPLT-TCM each with priority 0 (only priority available) as shown in column 1 of Table 5. Test A shall then be performed with all of the priorities (0, 1, 2, 3) shown in column 2, without first clearing the original call in progress. The required outcomes are shown in column 3.
- e) Duplex 64 kbit/s circuits shall be set up from the EUT (only priority 0 available). Test A shall then be performed with all the priorities (0, 1, 2, 3) shown in column 2 of Table 6, without first clearing the original call in progress. The required outcomes are shown in column 3.
- f) Duplex 64 kbit/s circuits shall be set up from the BPLT-TCM (only priority 0 available). Test A shall then be performed with all the priorities (0, 1, 2, 3) shown in column 2 of Table 7, without first clearing the original call in progress. The required outcomes are shown in column 3.
- g) Duplex 3,1k audio circuits shall be set up from the EUT (only priority 0 available). Test A shall then be performed with all the priorities (0, 1, 2, 3) shown in column 2 of Table 8, without first clearing the original call in progress. The required outcomes are shown in column 3.

- h) Duplex 3,1k audio circuits shall be set up from the BPLT-TCM (only priority 0 available). Test A shall then be performed with all the priorities (0, 1, 2, 3) shown in column 2 of Table 9, without first clearing the original call in progress. The required outcomes are shown in column 3.
- i) Duplex telephone calls shall be set up from the EUT with each of the priorities (0, 1, 2, 3) shown in column 1 of Table 10. 3,1k audio calls shall then be attempted from the EUT (only priority 0 available) without first clearing the original call in progress. The required outcomes are shown in column 3.
- j) Duplex telephone calls shall be set up from the BPLT-TCM with each of the priorities (0, 1, 2, 3) shown in column 1 of Table 11. 3,1k audio shall then be attempted from the EUT (only priority 0 available) without first clearing the original call in progress. The required outcomes are shown in column 3.

6.8.3 Required results

Telephone calls set up from the EUT shall automatically pre-empt on-going calls of a lower priority of any type, no matter whether set up originally from the EUT or from BPLT-TCM. Pre-empted calls shall clear in accordance with normal clearing procedures and the higher priority telephone call shall then be set up automatically. Results shall be in accordance with 6.1.4. Tables 2 to 11 indicate the required test results for items a) to j) of 6.8.2.

Table 2 – Pre-emption of telephone call set up from ship

Priority of original telephone call set up at ship	Priority of subsequent telephone call set up from ship (from another authorized extension)	Pre-emption required?
0	0	No
0	1	Yes
0	2	Yes
0	3	Yes
1	0	No
1	1	No
1	2	Yes
1	3	Yes
2	0	No
2	1	No
2	2	No
2	3	Yes
3	0	No
3	1	No
3	2	No
3	3	No

NOTE Inmarsat priorities are used.

Table 3 – Pre-emption of telephone call set up from shore

Priority of telephone call set up from shore	Priority of subsequent telephone call set up from ship (from another authorized extension)	Pre-emption required?
0	0	No
0	1	Yes
0	2	Yes
0	3	Yes
1	0	No
1	1	No
1	2	Yes
1	3	Yes
2	0	No
2	1	No
2	2	No
2	3	Yes
3	0	No
3	1	No
3	2	No
3	3	Yes ^a
^a A ship-originated distress call shall take precedence over a shore-originated call with distress priority.		
NOTE Inmarsat priorities are used.		

Table 4 – Pre-emption of facsimile call set up from ship

Priority of original facsimile call set up at ship	Priority of subsequent telephone call set up from ship (from another authorized extension)	Pre-emption required?
0	0	No
0	1	Yes
0	2	Yes
0	3	Yes
NOTE Inmarsat priorities are used.		

Table 5 – Pre-emption of facsimile call set up from shore

Priority of original facsimile call set up from shore	Priority of subsequent telephone call set up from ship (from another authorized extension)	Pre-emption required?
0	0	No
0	1	Yes
0	2	Yes
0	3	Yes
NOTE Inmarsat priorities are used.		

Table 6 – Pre-emption of 64 kbit/s call set up from ship

Priority of original 64 kbit/s call set up at ship	Priority of subsequent telephone call set up from ship (from another authorized extension)	Pre-emption required?
0	0	No
0	1	Yes
0	2	Yes
0	3	Yes
NOTE Inmarsat priorities are used.		

Table 7 – Pre-emption of 64 kbit/s call set up from shore

Priority of 64 kbit/s call set up from shore	Priority of subsequent telephone call set up from ship (from another authorized extension)	Pre-emption required?
0	0	No
0	1	Yes
0	2	Yes
0	3	Yes
NOTE Inmarsat priorities are used.		

Table 8 – Pre-emption of 3,1k audio call set up from ship

Priority of original 3,1k audio call set up at ship	Priority of subsequent telephone call set up from ship (from another authorized extension)	Pre-emption required?
0	0	No
0	1	Yes
0	2	Yes
0	3	Yes
NOTE Inmarsat priorities are used.		

Table 9 – Pre-emption of 3,1k audio call set up from shore

Priority of 3,1k audio call set up from shore	Priority of subsequent telephone call set up from ship (from another authorized extension)	Pre-emption required?
0	0	No
0	1	Yes
0	2	Yes
0	3	Yes
NOTE Inmarsat priorities are used.		

Table 10 – Non-pre-emption of high-priority ship-originated telephone call by subsequent lower priority ship-originated calls.

Priority of on-going telephone call	Type of subsequent call (Priority 0)	Pre-emption required?
0	3,1k audio	No
1	3,1k audio	No
2	3,1k audio	No
3	3,1k audio	No

Table 11 – Non-pre-emption of high-priority shore-originated telephone call by subsequent lower priority ship-originated calls

Priority of on-going telephone call	Type of subsequent call (Priority 0)	Pre-emption required?
0	3,1k audio	No
1	3,1k audio	No
2	3,1k audio	No
3	3,1k audio	No

6.9 Power supply

(See 5.4)

6.9.1 Purpose

To test the EUT for compliance with the power supply requirements as set out in IMO Resolution A.694(17) and detailed in IEC 60945 and the special requirements of 5.4.

6.9.2 Method of test

The national administration shall agree this test with Inmarsat at least 7 days before the test is performed. Inmarsat will make arrangements with a cooperating RCC and advise the national administration of its identity and associated RAN at least 24 h before testing commences.

The EUT shall be set to acquire an Inmarsat satellite. The EUT shall then be subjected to the power supply interruptions described in IEC 60945. Unwanted transmissions from the antenna shall be detected by means of a test antenna located in an antenna sidelobe and a spectrum analyser or broadband power meter. Alternatively, a coupler in the feeder to the antenna of the EUT may be used to deliver power to the test equipment.

Three minutes after each power supply interruption, a ship-originated priority 3 voice call shall be set up from the EUT to the cooperating RCC. At the end of each call, the call shall be cleared from the EUT.

6.9.3 Result required

During and after each power supply interruption, no unwanted transmissions shall be detected.

After each power supply interruption, there shall be no corruption of operational software and no essential data shall be lost.

The EUT shall recover after each power supply interruption in accordance with performance Criterion B of IEC 60945, within 3 min of power being restored.

Priority 3 test calls to the cooperating RCC shall be successful. Speech quality shall be good in both directions. Calls shall clear down successfully at the end of each call.

6.10 Interfaces

(See 5.4)

Where interfaces to external sensors and sources, which comply with IMO Resolutions and ITU Recommendations are provided (interfaces that conform to IEC 61162), these interfaces shall be tested in accordance with the relevant annex of IEC 61162, for example, Annex B of IEC 61162-1.

Any additional interfaces based on the IEC 61162 series shall be tested to the appropriate IEC 61162 standard.

Any critical or unique interface characteristics, for example, timing, resulting actions or equipment behaviour due to receipt or transmission of a sentence, shall be identified and the manufacturer should provide a detailed test method for each critical interface characteristic.

Annex A

(normative)

Requirements relating to installation

The equipment manual shall include all information necessary to determine whether the EUT complies with the IMO installation requirements.

A.1 Power supply

(MSC.130/A.5.1) *The ship earth station shall normally be powered from the ship's main source of electrical energy. In addition, it shall be possible to operate the ship earth station and all equipment necessary for its normal functioning, including the antenna tracking system, from an alternative source of energy.*

A.2 Antenna siting

(MSC.130/A.6.1) *It is desirable that the antenna be sited in such a position that no obstacle likely to significantly degrade the performance of the equipment appear in any azimuth down to an angle of elevation of -5° .*

(MSC.130/A.6.2) *The siting of the antenna needs careful consideration, taking into account the adverse effect of high levels of vibration which might be introduced by the use of a tall mast and the need to minimize shadow sectors. Objects, especially those within 10 m of the radome which cause a shadow sector of greater than 6° , are likely to significantly degrade the performance of the equipment.*

(MSC.130/A.6.3) *The above deck equipment shall be separated, as far as is practicable, from the antennae of other communication and navigation equipment.*

Annex B
(informative)

Reception of maritime safety information (MSI)

MSI is broadcast currently by means of the NAVTEX and SafetyNET systems. Inmarsat FB500 provides neither of these services. Reception of MSI is thus dependent on appropriate additional receiving equipment, for example, a SafetyNET receiver, an Inmarsat-C transceiver capable of receiving SafetyNET transmissions or a NAVTEX receiver, being included in the GMDSS installation. (See IEC 61097-4 and IEC 61097-6)

Annex C (informative)

List of Inmarsat FB500 type-approval tests

Table C.1 gives the tests which are performed during Inmarsat type approval. The requirements for the tests are given in the Inmarsat BGAN System Definition Manual. UT manufacturers are advised to make available Inmarsat type approval test results to national administrations on request.

Table C.1 – List of Inmarsat tests

1	Radiation Pattern	18	Tx Tuning Range
2	Polarisation	19	Tx Frequency Accuracy and Stability
3	Axial ratio	20	Modulator Performance
4	Pointing loss	21	Tx Burst Characteristics
5	G/T Determination	22	Reporting N/A
6	Rx Tuning Range	23	C/No Measurement & Report
7	QPSK Frame Acquisition	24	Tx Coding Performance
8	QPSK PER	25	Tx Burst Timing Accuracy and Stability
9	QAM frame acquisition	26	Transmitter Power Spectral Density
10	QAM PER	27	N/A
11	QPSK Selectivity	28	Code Rate Detection
12	QAM Selectivity	29	Doppler Compensation
13	Rx Dynamic Range	30	Handset Audio Levels & Bluetooth audio
14	EIRP	31	DTMF via audio channel tests
15	Tx Off Level	32	Echo Canceller tests
16	Spurious and Harmonics	33	Voice Codec testing using VCTS
17	Tx Phase Noise		

The UT should also comply with the protocol test defined as part of the Inmarsat FB500 type approval:

- Adaption layer
- Bearer connection layer
- Bearer control layer
- NAS
- ISDN

Bibliography

IEC 61097-4, *Global maritime distress and safety system (GMDSS) – Part 4: Inmarsat-C ship earth station and Inmarsat enhanced group call (EGC) equipment – Operational and performance requirements, methods of testing and required test results*

IEC 61097-6, *Global maritime distress and safety system (GMDSS) – Part 6: Narrowband direct-printing telegraph equipment for the reception of navigational and meteorological warnings and urgent information to ships (NAVTEX) – Operational and performance requirements, methods of testing and required test results*

ITU-R Recommendation BS.1284, *Methods for the subjective assessment of sound quality – General requirements*